

(d) Cross any portion of an unleased block(s).

[53 FR 10690, Apr. 1, 1998. Redesignated at 63 FR 29479, May 29, 1998, as amended at 63 FR 43881, Aug. 17, 1998; 65 FR 46096, July 27, 2000; 67 FR 35405, May 17, 2002]

§ 250.1002 Design requirements for DOI pipelines.

(a) The internal design pressure for steel pipe shall be determined in accordance with the following formula:

$$P = \frac{2(S)(t)}{D} \times (F)(E)(T)$$

For limitations see section 841.121 of American National Standards Institute (ANSI) B31.8 where—

P=Internal design pressure in pounds per square inch (psi).

S=Specified minimum yield strength, in psi, stipulated in the specification under which the pipe was purchased from the manufacturer or determined in accordance with section 811.253(h) of ANSI B31.8.

D=Nominal outside diameter of pipe, in inches.

t=Nominal wall thickness, in inches.

F=Construction design factor of 0.72 for the submerged component and 0.60 for the riser component.

E=Longitudinal joint factor obtained from Table 841.1B of ANSI B31.8. (See also section 811.253(d)).

T=Temperature derating factor obtained from Table 841.1C of ANSI B31.8.

(b)(1) Pipeline valves shall meet the minimum design requirements of American Petroleum Institute (API) Spec 6A, API Spec 6D, or the equivalent. A valve may not be used under operating conditions that exceed the applicable pressure-temperature ratings contained in those standards.

(2) Pipeline flanges and flange accessories shall meet the minimum design requirements of ANSI B16.5, API Spec 6A, or the equivalent. Each flange assembly must be able to withstand the maximum pressure at which the pipeline is to be operated and to maintain its physical and chemical properties at any temperature to which it is anticipated that it might be subjected in service.

(3) Pipeline fittings shall have pressure-temperature ratings based on stresses for pipe of the same or equivalent

material. The actual bursting strength of the fitting shall at least be equal to the computed bursting strength of the pipe.

(c) The maximum allowable operating pressure (MAOP) shall not exceed the least of the following:

(1) Internal design pressure of the pipeline, valves, flanges, and fittings;

(2) Eighty percent of the hydrostatic pressure test (HPT) of the pipeline; or

(3) If applicable, the MAOP of the receiving pipeline when the proposed pipeline and the receiving pipeline are connected at a subsea tie-in.

(d) If the maximum source pressure (MSP) exceeds the pipeline's MAOP, you must install and maintain redundant safety devices meeting the requirements of section A9 of API RP 14C (incorporated by reference as specified in § 250.198). Pressure safety valves (PSV) may be used only after a determination by the Regional Supervisor that the pressure will be relieved in a safe and pollution-free manner. The setting level at which the primary and redundant safety equipment actuates shall not exceed the pipeline's MAOP.

(e) Pipelines shall be provided with an external protective coating capable of minimizing underfilm corrosion and a cathodic protection system designed to mitigate corrosion for at least 20 years.

(f) Pipelines shall be designed and maintained to mitigate any reasonably anticipated detrimental effects of water currents, storm or ice scouring, soft bottoms, mud slides, earthquakes, subfreezing temperatures, and other environmental factors.

[53 FR 10690, Apr. 1, 1988. Redesignated at 63 FR 29479, May 29, 1998, as amended at 67 FR 51760, Aug. 9, 2002]

§ 250.1003 Installation, testing, and repair requirements for DOI pipelines.

(a)(1) Pipelines greater than 8-5/8 inches in diameter and installed in water depths of less than 200 feet shall be buried to a depth of at least 3 feet unless they are located in pipeline congested areas or seismically active areas as determined by the Regional Supervisor. Nevertheless, the Regional Supervisor may require burial of any

§ 250.1004

pipeline if the Regional Supervisor determines that such burial will reduce the likelihood of environmental degradation or that the pipeline may constitute a hazard to trawling operations or other uses. A trawl test or diver survey may be required to determine whether or not pipeline burial is necessary or to determine whether a pipeline has been properly buried.

(2) Pipeline valves, taps, tie-ins, capped lines, and repaired sections that could be obstructive shall be provided with at least 3 feet of cover unless the Regional Supervisor determines that such items present no hazard to trawling or other operations. A protective device may be used to cover an obstruction in lieu of burial if it is approved by the Regional Supervisor prior to installation.

(3) Pipelines shall be installed with a minimum separation of 18 inches at pipeline crossings and from obstructions.

(4) Pipeline risers installed after April 1, 1988, shall be protected from physical damage that could result from contact with floating vessels. Riser protection on pipelines installed on or before April 1, 1988, may be required when the Regional Supervisor determines that significant damage potential exists.

(b)(1) Pipelines shall be hydrostatically tested with water at a stabilized pressure of at least 1.25 times the MAOP for at least 8 hours when installed, relocated, uprated, or reactivated after being out-of-service for more than 1 year.

(2) Prior to returning a pipeline to service after a repair, the pipeline shall be pressure tested with water or processed natural gas at a minimum stabilized pressure of at least 1.25 times the MAOP for at least 2 hours.

(3) Pipelines shall not be pressure tested at a pressure which produces a stress in the pipeline in excess of 95 percent of the specified minimum-yield strength of the pipeline. A temperature recorder measuring test fluid temperature synchronized with a pressure recorder along with deadweight test readings shall be employed for all pressure testing. When a pipeline is pressure tested, no observable leakage shall be allowed. Pressure gauges and record-

30 CFR Ch. II (7-1-03 Edition)

ers shall be of sufficient accuracy to verify that leakage is not occurring.

(4) The Regional Supervisor may require pressure testing of pipelines to verify the integrity of the system when the Regional Supervisor determines that there is a reasonable likelihood that the line has been damaged or weakened by external or internal conditions.

(c) When a pipeline is repaired utilizing a clamp, the clamp shall be a full encirclement clamp able to withstand the anticipated pipeline pressure.

[53 FR 10690, Apr. 1, 1988; 53 FR 12227, Apr. 13, 1988; 57 FR 26997, June 17, 1992. Redesignated at 63 FR 29479, May 29, 1998]

§ 250.1004 Safety equipment requirements for DOI pipelines.

(a) The lessee shall ensure the proper installation, operation, and maintenance of safety devices required by this section on all incoming, departing, and crossing pipelines on platforms.

(b)(1)(i) Incoming pipelines to a platform shall be equipped with a flow safety valve (FSV).

(ii) For sulphur operations, incoming pipelines delivering gas to the power plant platform may be equipped with high- and low-pressure sensors (PSHL), which activate audible and visual alarms in lieu of requirements in paragraph (b)(1)(i) of this section. The PSHL shall be set at 15 percent or 5 psi, whichever is greater, above and below the normal operating pressure range.

(2) Incoming pipelines boarding to a production platform shall be equipped with an automatic shutdown valve (SDV) immediately upon boarding the platform. The SDV shall be connected to the automatic- and remote-emergency shut-in systems.

(3) Departing pipelines receiving production from production facilities shall be protected by high- and low-pressure sensors (PSHL) to directly or indirectly shut in all production facilities. The PSHL shall be set not to exceed 15 percent above and below the normal operating pressure range. However, high pilots shall not be set above the pipeline's MAOP.

(4) Crossing pipelines on production or manned nonproduction platforms which do not receive production from the platform shall be equipped with an